# tesa® Professional 74922 Self-adhesive Protection Paper

## Product Information

tesa® Self-adhesive Protection Paper – For large area protection and coverage

### Product Description

tesa® Self-adhesive Protection Paper is a professional-quality craft paper ideal for large-area protection and coverage during painting or renovation jobs. Offering a smooth and effective protection against paint spills and scratches on various surfaces such as windowsills, stairs, floors, and countertops. Easy to apply, reposition and remove without leaving any adhesive residue, making clean-up hassle-free.

### Sustainable Aspects

tesa® Self-adhesive Protection Paper is made with paper from well-managed FSC®-certified forests, recycled materials, and other controlled sources and it meets the FSC® Standards.

The communication of the FSC® certification is strictly limited to sales organizations that are FSC® certified (FSC® C148769).

### Product Features

- Easy application to protect against dirt, dust, and paint splashes even on the most sensitive surfaces
- Easy removal without leaving any residues for up to 3 months
- Repositionable multiple times
- Fully coated for enhanced durability and performance
- Smooth and thick craft paper that prevents paint bleed through
- Scope of delivery: 1 x roll of tesa® Self-adhesive Protection Paper

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- Paper — Recycled content of backing
- Type of adhesive — water-based acrylic
- Total thickness — 140 µm



**For latest information on this product please visit http://l.tesa.com/?mp=74922**

# tesa® Professional 74922 Self-adhesive Protection Paper

## Product Information

### Properties/Performance Values

- Elongation at break 1 %
- Tensile strength 50 N/cm
- Application temperature from 5 °C
- Application temperature to 60 °C
- Backing weight 90 g/m²
- Easy to remove yes
- Humidity resistance low
- Material Paper
- Material of masking coverage paper
- Residue-free removability yes
- Residue-free removable after... 90 days
- Solvent free yes
- Suitable for rough surfaces no
- Suitable for sensitive surfaces yes
- Tear resistance no
- UV resistance indoor 4 weeks
- Water resistance no

### Adhesion to Values

- Steel 0.4 N/cm

## Certificates

**Sustainability Certificates**
FSC® Certified

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

**For latest information on this product please visit http://l.tesa.com/?mp=74922**